## 500 $\mu\text{L},$ Model 1750 LT SYR, NDL Sold Separately

500 µL, Model 1750 LT SYR, NDL Sold Separately



Part Number/REF: 81201 Unit Price: Quote Required

## Specifications

Volume	500 µL
Syringe Type	Gastight
Syringe Series	1700
Termination	Luer Tip (LT)
Needle	Kel-F Hub
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Std. Needle Dead Volume	N/A
Fluid Path	Borosilicate glass, PTFE
Fluid Path Autoclavable	Borosilicate glass, PTFE Yes to 115°C
Autoclavable	Yes to 115°C
Autoclavable Gas Sterilizable	Yes to 115°C Yes
Autoclavable Gas Sterilizable Pressure	Yes to 115°C Yes 700 psig (48.3 bar)
Autoclavable Gas Sterilizable Pressure Maximum Temperature	Yes to 115°C Yes 700 psig (48.3 bar) 115°C / 239°F
Autoclavable   Gas Sterilizable   Pressure   Maximum Temperature   Minimum Temperature	Yes to 115°C Yes 700 psig (48.3 bar) 115°C / 239°F 10°C / 50°F
Autoclavable   Gas Sterilizable   Pressure   Maximum Temperature   Minimum Temperature   Barrel Inner Diameter	Yes to 115°C   Yes   700 psig (48.3 bar)   115°C / 239°F   10°C / 50°F   0.128 inches (3.26 mm)

## Accessories

Part Number/REF	Description	Unit Price
1169-01	Plunger Assembly N RN 1750	Quote Required

## Accessories

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.