## 1 L, Model S1000 TLL SYR, NDL Sold Separately

1 L, Model S1000 TLL SYR, NDL Sold Separately



Part Number/REF: 86312 Unit Price: Quote Required

## Specifications

Volume	1L
Syringe Type	Gastight
Syringe Series	Super Syringe
Termination	PTFE Luer Lock (TLL)
Needle	Metal (N) or Kel-F
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Std. Needle Dead Volume	N/A
Fluid Path	Buna-N, Nickel plated brass, PTFE, Silicone
Fluid Path  Autoclavable	Buna-N, Nickel plated brass, PTFE, Silicone  No
Autoclavable	No
Autoclavable  Gas Sterilizable	No Yes
Autoclavable  Gas Sterilizable  Pressure	No Yes 30 psig (2.1 bar)
Autoclavable  Gas Sterilizable  Pressure  Maximum Temperature	No Yes 30 psig (2.1 bar) 80°C / 176°F
Autoclavable  Gas Sterilizable  Pressure  Maximum Temperature  Minimum Temperature	No Yes 30 psig (2.1 bar) 80°C / 176°F 0°C / 32°F
Autoclavable  Gas Sterilizable  Pressure  Maximum Temperature  Minimum Temperature  Barrel Inner Diameter	No Yes 30 psig (2.1 bar) 80°C / 176°F 0°C / 32°F 3.44 inches (87.4 mm)

## Accessories

Part Number/REF	Description	Unit Price
18026	TLL Connector S0500 S1000 S1500 S2000	Quote Required

http://www.hamiltoncompany.com/products/syringes-and-needles/general...

of Hamilton Company or its licensors in the U.S. and/or other countries.

2 of 2