



8GHz RF EMF Strength Meter

High Frequency measurement for EMF

Monitor high frequency radiation in the 10MHz to 8GHz frequency range

Features:

- For electromagnetic field strength measurement including mobile phone base station antenna radiation, RF power measurement for transmitters, wireless LAN (Wi-Fi) detection/installation, wireless communication applications (CW, TDMA, GSM, DECT) and microwave leakage
- Measurement optimized for 900MHz, 1800MHz, 2.7GHz, 3.5GHz and 8GHz
- Non-directional (isotropic) measurement with three-channel (triaxial) measurement probe
- Max Hold and Average functions
- Manual store/recall up to 99 sets
- · Level exceed audible alarm with user selectable threshold
- · Complete with 9V battery and carrying case



Applications

- RF electromagnetic wave field strength measurements
- Mobile phone base station antenna radiation power density measurement
- · Radiation safety level tests
- Locating RF "Hot Spots" in the workplace or at home
- Microwave oven leakage tests
- RF "Electrosmog" detection
- Wireless network (Wi-Fi) RF detection



| Specifications | |
|------------------|--|
| Sensor Type | Electric Field |
| Frequency Range | 10MHz to 8GHz (optimized for 900MHz, 1800MHz, 2.7GHz, 3.5GHz & 8GHz) |
| Units of Measure | mV/m, V/m, μA/m, mA/m, μW/m², mW/m², W/m², μW/cm², mW/cm² |
| Measuring Ranges | 20mV/m to 108.0V/m |
| | 53μA/m to 286.4mA/m |
| | 1μW/m² to 30.93W/m² |
| | 0μW/cm² to 3.093mW/cm² |
| Resolution | 0.1mV/m, 0.1μA/m, 0.1μW/m², 0.001μW/cm² |
| Audible Alarm | Adjustable threshold with On/Off |
| Memory | Manual store/recall of 99 sets |
| Dimensions | 2.6x2.4x9.7" (67x60x247xmm) |
| Weight | 8.8oz (250g) |
| | |

Ordering Information:

480846RF Electromagnetic Field Strength Meter

